

TUNING SPECIFICATIONS

Make: Holden		Bore: 101.6000 mm
Engine: VS 5.0L	Holden VS (HSV) V/8 5.0L	Stroke: 76.8350 mm
Cylinders: 8	Valve Layout:	Fuel Type: P
		Capacity: 4988 cc

Tuning Settings

Firing Order:	1-2-7-8-4-5-6-3		
Plug Gap:		mm	
Points Gap:	mm		
Ignition Timing:	TDC +/-	@	RPM
Location:			
Dwell Angle:	-	o	
Centrifugal Advance:			
Centrifugal Advance Intermediate:			
Centrifugal Advance Maximum:			
Vacuum Advance Start:			
Vacuum Advance Intermediate:			
Vacuum Advance Maximum:			
Total Advance:			
Tapets Inlet:	-	mm	H
Tapets Exhaust:	-	mm	

Engine Information

Compression Ratio:	to 1		
Compression Pressure:	kPa @		
Maximum Power:	185 kW @	0	RPM
Maximum Torque:	Nm @		RPM
Oil Pressure:	276 -	kPa @	2,000 RPM
Distributor:			
Coil:			
Primary Resistance:			
Ballast Resistor:			

Notes

Min oil Press: 48 kpa @ 500rpm

DISCLAIMER OF WARRANTIES

Although the information contained within this report has been obtained from sources, generally believed to be reliable, no warranty (expressed or implied) can be made to its accuracy or completeness, nor is any responsibility assumed by the Engine Reconditioners Association (ERA-A) or anyone connected with it for loss or damage suffered through reliance on any information contained in this volume. Specifically, no warranty of merchantability or fitness for a particular purpose or any other warranty is made or to be implied with respect to this disclaimer, and no person has the authority to modify such limitation except in writing signed by a corporate officer of the ERA-A.